

OFFER: Sulphate Resistant Cement

Origin: Pakistan
Packaging: in bulk

Production capacity: 15,000 MT per month
Standard: BS - 4027/1980

Chemical analysis	SRC (Power)	PS - 612/1989 (R)	BS - 4027/1980
LSF	0.95	1.02 - 0.66	1.02 - 0.66
C ₃ A	2.20	3.50 (Max)	3.50 (Max)
SO ₃	2.20	2.50 (Max)	2.50 (Max)
L.O.I.	1.20	3.00 (Max)	3.00 (Max)

Physical analysis	SRC (Power)	PS - 612/1989 (R)	BS - 4027/1980
Fineness	2800 M ² /kg	2500 M ² /kg	2500 M ² /kg
Soundness	1 mm (Max)	5 mm (Max)	5 mm (Max)
Setting time			
- Initial	123 Mts	45 Mts (Min)	45 Mts (Min)
- Final	196 Mts	10 Hrs (Max)	10 Hrs (Max)
Compressive strengths			
- 3 days	23 N/mm ²	15 N/mm ²	20 N/mm ²
- 7 days	32 N/mm ²	23.5 N/mm ²	No limit
- 28 days	40 N/mm ²	34 N/mm ²	39 N/mm ²